



## Colour Offering



**HG217** BLACK



**HG23** CASHMERE DUSK



**HG18** COTTON MIST



**HG22** WARM ALPACA

PÜRDECO™ GlossTouch™ laminated panels are modern, contemporary and have a mirror-like finish. This collection of neutral solid colours are vibrant and fresh.

Beautiful on their own, or paired with other panel products such as wood, TFL woodgrains or ultra matte specialty panels like VelourTouch™. These high gloss panels add a high-end European feel to any residential or commercial project.

The GlossTouch™ Collection of colours has been custom matched to the VelourTouch™ Ultra matte collection for ease of designing with multiple materials.

## Specialty Panels



5/8" & 3/4" PANELS FOR CASEGOODS AND FLAT PANEL DOORS

STANDARD PANEL MATRIX	PANEL SIZE	SHEETS/BUNDLE	MINIMUM ORDER (SHEETS)
5/8" MDF	49" x 109" (nom 4' x 9')	50	200
3/4" MDF	49" x 109" (nom 4' x 9')	40	200

Standard panel size is 4' x 9' for 5/8" and 3/4"

- Sizes outside this matrix can be made available
- All panels are good 2 sides
- All panels have protective peel coat on high gloss surfaces
- Possibility of white or black textured surface on 2<sup>nd</sup> side, specify the following:
  - HG18 Cotton Mist/O17 White
  - HG217 Black/O16 Black

## Cleaning

High Gloss films are ready for immediate use after removal of the protective film.

1. Use mild cleaning solutions. Common, diluted household cleaners recommended for plastic surfaces are suitable (ionic or non-ionic surfactants). Any residue from the cleaning solution can be removed with plain water and dried with a soft cloth.
2. Due to the excellent solvent resistance, highly concentrated Isopropanol or even Acetone can be used with care to remove local soiling. Avoid any strong rubbing or high pressure.
3. Do not use abrasive cleaners or sponges or steam cleaning tools.
4. As a precaution, test cleaning solution in an inconspicuous area, minimizing the time of exposure and amount of cleaning solution in order to prevent any damage to the surface.

## Physical Properties Test Results

PROPERTIES	STANDARD	UNIT	VALUES
Gloss Level (Target)	DIN67530 (60°)		≥85
Lightfastness (Blue Scale)	ISO 105-B02	BWS	6 - 7
Chemical Resistance	DIN 68861-1 - T1 EN12720	Class	1B
Scratch Resistance (Erichsen 413)	DIN 68861 - T4	Level	4F (0.5 N)
Scratch Resistance	CEN/TS16611 Martindale Type B	Level	4 scale from 1 (worst) - 5 (best)
Resistance to Dry Heat	DIN 68861-T7	Class	7D (70°C)
Wet Heat	DIN 68861-T8	Class	8B (70°C)

**Note:** GlossTouch™ laminated panels can be used for many different applications. Please ensure this product matches the specifications that you require for your building projects. GlossTouch™ laminated panels are intended for vertical, light duty surfaces.



Please contact your sales representative for additional information if required and for edgebanding cross references if necessary.